



## REG-X Close-range Plate Camera



- ▶ **Ambient Rejection Technology captures plates 24/7 in day or dark conditions up to 80 km/h (50 mph)**
- ▶ **Capture range 4.5 to 7.6 m (15 to 25 ft)**
- ▶ **400 TVL LXR B/W CCD for high contrast plate capture**
- ▶ **Reliable performance under any ambient lighting conditions**
- ▶ **Cable-managed bracket, conduit compatible**
- ▶ **IP66 compliant for extreme weather performance**
- ▶ **Discreet, compact and easy to install**
- ▶ **Connects directly to industry standard DVRs**
- ▶ **Installer-friendly design**

Based on award-winning technology, the REG-X delivers absolute performance in close-range number plate capture applications.

Precision engineered to deliver irrefutable plate images both day and night, REG-X features Ambient Rejection Technology to ensure consistent, reliable plate capture from close range.

A powerful 850 nm infrared array ensures that REG-X works under all ambient lighting conditions, including complete darkness and headlight glare. The 16 mm fixed lens provides effective 400 TVL capture from a range of 4.5 to 7.6 m (15 to 25 ft.)

REG-X integrates seamlessly with industry standard DVRs and is IP66 compliant for harsh outdoor environments. Discreet, compact and installer-friendly, REG-X is suitable in both 12 V and 24 V environments.

IR Wavelength	850 nm
Lens	16 mm
Video Signal Output	1 Vpp, 75 ohm
S/N Ratio	> 48 dB
Environmental	IP66
Operating temperature range	-30 °C to +55 °C (-22 °F to +131 °F)
Dimensions	96 x 219 mm (3.8 x 8.6 in ) (Ø x L)
Weight	1.2 kg (2.7 lb)
Construction	Aluminum
Finish	Anodized black
Input voltage range	12 to 24 VDC or 24 VAC
Power consumption	6.5 W

### Technical Specifications

Operational Range	4.5 to 7.6 m (15 to 25 ft)
Image Sensor	1/3 in LXR, mono
Resolution	400 TVL
Mono Camera CCD Effective Pixels	CCIR: 795 x 596 (H x V), EIA: 811 x 508 (H x V)
Minimum Illumination	0 lx - camera operates in complete darkness

### Ordering Information

<b>REG-X-816-XE Close-range Plate Camera</b> REG X close-range LPR, 400 TVL, 1/3 in LXR, 15 to 25 ft, 16 mm lens, EIA, psu sold separately.	<b>REG-X-816-XE</b>
---	---------------------

<b>REG-X-816-XC Close-range Plate Camera</b> REG X close-range LPR, 400 TVL, 1/3 in LXR, 4.5 to 7.6 m (15 to 25 ft), 16 mm lens, CCIR, psu sold separately.	<b>REG-X-816-XC</b>
--	---------------------

### Accessories

<b>UPA-2430-60 Power Supply</b> 120VAC, 60Hz, 24VAC, 30VA Out	<b>UPA-2430-60</b>
--	--------------------

<b>UPA-2420-50 Power Supply</b> 220VAC, 50Hz, 24VAC, 20VA Out	<b>UPA-2420-50</b>
--	--------------------

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: +31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2600  
Fax: +65 6571 2698  
apr.securitysystems@bosch.com  
www.boschsecurity.com

### Represented by